



- SPECIFICATIONS
- ▲ Voltage Rating : 125V AC/DC
 - Current Rating : 1.0 A AC/DC
 - Withstanding Voltage : 250V AC/minute
 - Insulation Resistance : 100M Ω min
 - Temperature Range : - 25°C to + 85°C
 - Contact Resistance : 20m Ω max
- WAFER
- ▲ Part No. : 2WB1259-XX-XX(XX)-XX XX-XX
① ② ③ ④ ⑤ ⑥

- Code No :
- ① Poles : 2~30
 - ② Mylar : Blank : Without Mylar
ML : With Mylar
 - ③ Contact Plated : Blank : Tin Plated
G : Gold Plated
 - ④ Base Material : Blank : Nylon PA 9T UL94V-0
H1 : Nylon 6T / 66 UL94V-0
 - ⑤ Base Color : Blank : Nature
BK : Black
 - ⑥ Halogen : Blank : Normal
NH : Non - Halogen
 - Material : Contact : Copper Alloy
Solder Nail : Brass
Base : Refer Above Options
 - Packing : Tape/Reel

Poles	Dimensions			
	A	B	C	D
02	1.25	7.65	3.80	
03	2.50	8.90	5.05	
04	3.75	10.15	6.30	2.50
05	5.00	11.40	7.55	3.75
06	6.25	12.65	8.80	5.00
07	7.50	13.90	10.05	6.25
08	8.75	15.15	11.30	7.50
09	10.00	16.40	12.55	8.75
10	11.25	17.65	13.80	10.00
11	12.50	18.90	15.05	11.25
12	13.75	20.15	16.30	12.50
13	15.00	21.40	17.55	13.75
14	16.25	22.65	18.80	15.00
15	17.50	23.90	20.05	16.25
16	18.75	25.15	21.30	17.50
17	20.00	26.40	22.55	18.75
18	21.25	27.65	23.80	20.00
19	22.50	28.90	25.05	21.25
20	23.75	30.15	26.30	
21	25.00	31.40	27.55	
22	26.25	32.65	28.80	
23	27.50	33.90	30.05	
24	28.75	35.15	31.30	
25	30.00	36.40	32.55	22.50
26	31.25	37.65	33.80	
27	32.50	38.90	35.05	
28	33.75	40.15	36.30	
29	35.00	41.40	37.55	
30	36.25	42.65	38.80	

TOLERANCE	LTR	REVISION RECORD	NAME	DATE
.0	±0.30	▲8 鍍層變更	林文泰	2010/06/21
.00	±0.20	▲9 增加料號選項	吳弘文	2012/06/20
.000	±0.10	▲10 產品外觀修正	吳弘文	2012/11/23
ANGLE		▲11 修正PCB Layout A尺寸	吳弘文	2013/06/20
0°	±1°	▲12 增加Pin define 標示	吳弘文	2015/09/15
.0°	±	▲13 表格D尺寸更正	吳弘文	2016/03/24
SHEET	1/1			

Singatron Enterprise Co., Ltd.

TITLE 1.25mm Crimp Style Connectors

DWN 吳弘文 PART NO. 2WB1259-XX-XX(XX)-XX XX-XX

CHKD 周慈雲 SCALE 1:1 UNIT: mm

APVD 張育瑞 SIZE: A3 SHEET: 1 OF 1 REV: a13

CUSTOMER COPY