



SECTION:A-A

SPECIFICATIONS

- Voltage Rating : 250V AC/DC
- Current Rating : 3A AC/DC
- Withstanding Voltage : 1,000V AC/minute
- Insulation Resistance : 1,000M Ω min
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20m Ω max.

HOUSING

- Part No. : 2WB8002-XX(XX)

① Poles : 2 - 15

② Material :

Blank:Nylon 66 UL94V-2

△ SM: SCHULAMID (Polyamide 6 UL94V-2)

- Q' ty : 1,000 pcs./Bag

Poles	Dimensions(mm)	
	A	B
2	2.50	5.80
3	5.00	8.30
4	7.50	10.80
5	10.00	13.30
6	12.50	15.80
7	15.00	18.30
8	17.50	20.80
9	20.00	23.30
10	22.50	25.80
11	25.00	28.30
12	27.50	30.80
13	30.00	33.30
14	32.50	35.80
15	35.00	38.30

TOLERANCE	LTR	REVISION RECORD	NAME	DATE	LTR	REVISION RECORD	NAME	DATE
.0	±0.30	①			⑧			
.00	±0.20	②	套新圖框，刪除GP料號	張逸維 2012/11/23	⑨			
.000	±0.10	③	增加模號與部分標註說明	林宛盈 2013/10/09	⑩			
ANGLE		④	增加SM（舒爾曼料）選項	曾慶根 2015/10/23	CUSTOMER Conforms to The RoHS Instruction			
0°	±1°	⑤						
.0°	±	⑥						
SHEET	1/1	⑦						

Singatron Enterprise Co., Ltd.

TITLE	2.50mm Crimp Style Connectors Housing			
DWN	曾慶根	PART NO.	2WB8002-XX(XX)	
CHKD	周家慶	SCALE	1:1	UNIT: mm
APVD	張育瑞	SIZE: A3	SHEET: 1 OF 1	REV: a4
CUSTOMER COPY				