



P/N LEGEND

①	②	③	④
2WBA2004	HB-2XNP	XXX	
① Series No.	② Connector type: H=Housing B Type	③ No. of circuits	④ Option code:
			Blank=Standard

SPECIFICATIONS

Current Rating: 3A AC,DC
Voltage Rating: 250V AC,DC
Temperature Range: -25°C ~ +85°C
Contact Resistance: 10mΩ Max.
Insulation Resistance: 1000MΩ Min.
Withstanding Voltage: 800V AC/minute
Material: Nylon 66,UL94V-0
Color: Natural(White)

Circuit No.	Dimensions A	Dimensions B	Circuit No.	Dimensions A	Dimensions B
02P	2.00	5.90	12P	22.00	25.90
03P	4.00	7.90	13P	24.00	27.90
04P	6.00	9.90	14P	26.00	29.90
05P	8.00	11.90	15P	28.00	31.90
06P	10.00	13.90	16P	30.00	33.90
07P	12.00	15.90	17P	32.00	35.90
08P	14.00	17.90	18P	34.00	37.90
09P	16.00	19.90	19P	36.00	39.90
10P	18.00	21.90	20P	38.00	41.90
11P	20.00	23.90	22P	42.00	45.90

Singatron Enterprise Co., Ltd.

TITLE	2.00mm PITCH HOUSING
DWN	2020.08.01.08
CHKD	2020.08.01.08
APVD	2020.08.01.08
REV.	DESCRIPTION
DATE	DATE
NAME	NAME
GENERAL TOLERANCE	ANGLE±
X. X±0.25	X. XX±0.15
X. XXX±0.05	
SCALE 1:1	UNIT: mm
SIZE: A3	SHEET:1 OF 1
REV: A3	

CUSTOMER COPY

REV.	DESCRIPTION	DATE	NAME	GENERAL TOLERANCE	ANGLE±
A3	EN20200707357	2020.08.21	黃培軍	X. X±0.25	
A2	EN1203300088	2012.03.30	陳錦展	X. XX±0.15	
				X. XXX±0.05	