



**SPECIFICATIONS**  
 Current Rating: 3A AC,DC  
 Voltage Rating: 250V AC,DC  
 Temperature Range: -25°C ~ +85°C  
 Contact Resistance: 30mΩ Max.  
 Insulation Resistance: 1000MΩ Min.  
 Withstanding Voltage: 650V AC/minute  
 Pin Material: Brass/Gold-flash  
 Solder Tabs: Brass/Gold-flash  
 Material: Nylon 6T,UL94V-0  
 Color: Natural(Beige)

**Ordering Information & Dimensions**

PART NO.	Dimensions	
	A	B
2WBA2005WV-S-02P	2.00	8.50
2WBA2005WV-S-03P	4.00	10.50
2WBA2005WV-S-04P	6.00	12.50
2WBA2005WV-S-05P	8.00	14.50
2WBA2005WV-S-06P	10.00	16.50
2WBA2005WV-S-07P	12.00	18.50
2WBA2005WV-S-08P	14.00	20.50
2WBA2005WV-S-09P	16.00	22.50
2WBA2005WV-S-10P	18.00	24.50
2WBA2005WV-S-11P	20.00	26.50
2WBA2005WV-S-12P	22.00	28.50
2WBA2005WV-S-13P	24.00	30.50
2WBA2005WV-S-14P	26.00	32.50
2WBA2005WV-S-15P	28.00	34.50

**Singatron Enterprise Co., Ltd.**

GENERAL TOLERANCE	
X.X±0.25	ANGLE±
X.XX±0.15	
X.XXX±0.05	

TITLE		2.00mm PITCH 180 WAFER-SMT TYPE WITHOUT BOSS	
DWN	唐騰鳳	PART NO.	2WBA2005WV-S-XP
CHKD	陳彥池	SCALE	1:1
APVD	陳彥池	SIZE	A3
		SHEET	1 OF 1
		REV	A1
<b>CUSTOMER COPY</b>			