



03P~12P

02P

P/N LEGEND

2WBC3030 HF-XP N 0 X NP N 00 G

- ① Series No.
- ② Connector type: HF=Receptacle
- ③ No. of circuits
- ④ N=Halogen Free
- ⑤ Material: 0=Nylon 66-V0
- ⑥ Color: W=White R=Red B=Black
- ⑦ Plating code: NP=Non-plating
- ⑧ Plating code: N=Non-plating
- ⑨ Option code:
00=Standard
- ⑩ Packing code: G=Bag

SPECIFICATIONS

Current Rating: 5A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: -25°C ~ +85°C
 Contact Resistance: 10mΩ Max
 Insulation Resistance: 1000MΩ Min
 Withstanding Voltage: 1500V AC/minute
 Material: Nylon 66,UL94V-0
 Color: White Black or Red

Circuit No.	Dimensions	
	A	B
02P	3.00	6.80
03P	6.00	9.80
04P	9.00	12.80
05P	12.00	15.80
06P	15.00	18.80
07P	18.00	21.80
08P	21.00	24.80
09P	24.00	27.80
10P	27.00	30.80
11P	30.00	33.80
12P	33.00	36.80

Singatron Enterprise Co., Ltd.

TITLE	3.00mm PITCH HOUSING-RECEPTACLE, SINGLE ROW, MICRO-FIT		
DWN	黄模有	PART NO.	2WBC3030HF-XPXXXXXXXXX
CHKD	2014.07.07	SCALE 1:1	UNIT: mm
APVD	董正一	SIZE: A3	SHEET: 1 OF 1 REV: A0

CUSTOMER COPY

REV.	DESCRIPTION	DATE	NAME	GENERAL TOLERANCE	ANGLE±
A0	NEW RELEASE	2014.07.07	黄模有	X. X±0.25	ANGLE±
				X. XX±0.15	
				X. XXX±0.05	