



SPECIFICATIONS
 Current Rating: 5A AC,DC
 Voltage Rating: 250V AC,DC
 Temperature Range: $-25^{\circ}\text{C} \sim +85^{\circ}\text{C}$
 Contact Resistance: 10m Ω Max
 Insulation Resistance: 1000M Ω Min
 Withstanding Voltage: 1500V AC/minute
 Material: Nylon 66,UL94V-2
 Color: Black

Ordering Information & Dimensions

PART NO.	Dimensions	
	A	B
2WBC3030HM-2X01P	---	3.85
2WBC3030HM-2X02P	3.00	6.85
2WBC3030HM-2X03P	6.00	9.85
2WBC3030HM-2X04P	9.00	12.85
2WBC3030HM-2X05P	12.00	15.85
2WBC3030HM-2X06P	15.00	18.85
2WBC3030HM-2X07P	18.00	21.85
2WBC3030HM-2X08P	21.00	24.85
2WBC3030HM-2X09P	24.00	27.85
2WBC3030HM-2X10P	27.00	30.85
2WBC3030HM-2X11P	30.00	33.85
2WBC3030HM-2X12P	33.00	36.85

Singatron Enterprise Co., Ltd.			
TITLE	3.00mm PITCH HOUSING-PLUG, MICRO-FIT		
DWN	董正一	PART NO. 2WBC3030HM-2XNP	
CHKD	2001.02.01	SCALE 1:1	UNIT: mm
APVD	董正一	SIZE: A3	SHEET: 1 OF 1 REV: B1
CUSTOMER COPY			

REV.	DESCRIPTION	DATE	GENERAL TOLERANCE	ANGLE
B1	REVISE	2007.04.16	X.X \pm 0.25	ANGLE \pm
B0	NEW RELEASE	2005.12.14	X.XX \pm 0.15	
			X.XXX \pm 0.05	