


A-A SEC



B-B SEC

■ SPECIFICATIONS

- Voltage Rating : 250V AC/DC
- Current Rating : 3A AC/DC
- Withstanding Voltage : 1,500V AC/minute
- Insulation Resistance : 1,000MΩ min
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20mΩ max

■ TERMINAL

- Part No. : 2WT1114-04HT
- Applicable Wires : AWG# 16 - 22
- Material : Brass
- Finish : Tin Plated
- Thickness : 0.25mm
- Q' ty : 7,000 pcs./Reel

TOLERANCE		LTR	REVISION RECORD	DATE	LTR	REVISION RECORD	DATE
.0	±0.3	ECR	RoHS Compliant	07/01/04			
.00	±0.2	ECR	DG 200604-010	06/04/21			
.000	±0.1	ECR	200708-007	07/08/08			
ALL	±	ECR	200708-011	07/08/10			
ANGLE					CUSTOMER		
0°	±				Conforms to The RoHS Instruction		
.0°	±						

Singatron Enterprise Co., Ltd.

TITLE	5.08mm Disk Drive Power Connectors Terminal			
DWN	曾慶根	PART NO.	2WT1114-04HT	
CHKD	周家慶	SCALE	1:1	UNIT: mm
APVD	張育瑞	SIZE: A3	SHEET: 1 OF 1	REV: a5

CUSTOMER COPY