



- **SPECIFICATIONS**
- Current Rating : 1A AC/DC
- Withstanding Voltage : 500V AC/minute
- Insulation Resistance : 500M Ω min
- Temperature Range : - 25 °C to + 85 °C
- Contact Resistance : 20m Ω max
- **TERMINAL**
- Part No. : 2WT1173-TXX
- ① Blank: Ni>10u", Sn>50u" 先鍍後沖
- 2: Ni>30u", Sn>100u"
- Applicable Wires : AWG#28-32
- Material : Phos. Bronze
- Thickness : 0.2mm
- Q'ty : 10,000pcs./Reel

產品收料圖

TOLERANCE	LTR	REVISION RECORD	NAME	DATE	LTR	REVISION RECORD	NAME	DATE
.0	△	按上海圖面修改內部圖面公差	吳小平	2016/06/16	△			
.00	△				△			
.000	△				△			
<b>ANGLE</b>								
0°	△				△			
±1°	△				△			
±	△				△			
SHEET	1/1							

TITLE	DATE	APVD	CHKD	APVD
1.50mm Crimp Style Connectors TER		張育瑞	周家慶	張育瑞
DWN	吳小平	SCALE	1:1	SIZE
CHKD	周家慶	UNIT	mm	SHEET
APVD	張育瑞	REV	01	OF

CUSTOMER	CONFORMS TO THE ROHS INSTRUCTION

