



REV.	ECN NO.	REVISIONS	REV.DRAWN	DATE
I	----	依客户要求, 增加开口尺寸	Sunquan	2010/05/28
J	11041	依客户要求, 修改卡钩高度及形状	Asimo	2011/12/27
K	----	尺寸0.10 ⁰ _{-0.04} 变更为0.06±0.03	YangSong	2015/12/15
L	----	整理电镀规范	YangSong	2019/05/07
M	----	更改实物与图纸一致	YangSong	2020/07/17

- SPECIFICATIONS:
- VOLTAGE RATING: 50V AC/DC
 - CURRENT RATING: 1A, AC/DC
 - WITHSTANDING VOLTAGE: 500V AC/DC
 - INSULATION RESISTANCE: 100MΩ Min.
 - TEMPERATURE RANGE: -25^oC~+85^oC
 - CONTACT RESISTANCE: INITIAL VALUE: 20mΩ Max. AFTER ENVIRONMENTAL TESTING: 40mΩ Max.

- NOTES:
- MATERIAL: PHOS.BRONZE(C5210-SH T=0.12)
 - Q'TY: 15,000 PCS/REEL
 - APPLICABLE WIRES: AWG#32~28
 - PART No. 2WT1253-TXX

TIN PLATED 先镀后冲 BLANK: Sn>50^oi" Ni>10^oi"
 先冲后镀 2: Sn>100^oi" Ni>30^oi"
 4: Sn>50^oi" Ni>10^oi"
 GOLD PLATED G0: Au>0.8^oi" Ni>30^oi"
 G1: Au>3.0^oi" Ni>30^oi"

符合环境管理物质

Singatron Enterprise Co., Ltd.			
X. ± 0.40	X.* ± 5.0°	TITLE	1.00mm Crimp Style Connector
.X ± 0.30	.X* ± 2.0°	DWN	Asimo PART NO. 2WT1253-TXX
.XX ± 0.20	.XX* ± 1.0°	CHKD	2010/03/23 SCALE 1:1 UNIT: mm
.XXX± 0.10	.XXX*± --	APVD	SIZE: A3 SHEET:1 OF 1 REV: M
CUSTOMER COPY			