

SPECIFICATIONS


- . Voltage Rating : 125V AC/DC
- . Current Rating : 1A AC/DC
- . Withstanding Voltage : 250V AC/minute
- . Insulation Resistance ; 100MΩ min
- . Temperature Range : -40°C to +85°C
- . Contact Resistance : 20mΩ max

TERMINAL


. Part No Legend: 2WT1258-TXX

- Tin Plated**
- 2: Sn>100u" Ni>30u"
 - 3: Sn>150u" Ni>50u"
 - △4: Sn>50u" Ni>10u"
- Gold Plated**
- G0: Au>0.8u" Ni>30u"
 - G1: Au>3u" Ni>30u"
 - G2: Au>5u" Ni>50u"
 - G3: Au>8u" Ni>50u"
 - G4: Au>15u" Ni>50u"


- . Applicable Wires :AWG#28-32
- . Material : Phos. Bronze
- . Finish : Tin/Gold Plated
- . Thickness : 0.15mm
- . Q'ty : 15,000pcs/Reel




SECTION:C-C



SECTION:B-B



SECTION:A-A



TOLERANCE		REV	ECN.NO.	REVISIONS	REV.DRAWN	DATE		
X.±	0.50	X.°	5.0°	C	/	增加剖面标识	CARRY	08-01/18
.X±	0.30	.X°	2.0°	D	/	增加镀层测点标识	hejihuai	09-02/16
.XX±	0.20	.XX°	1.0°	E	/	增加尺寸标注	sunquan	10-08/16
.XXX±	0.10	.XXX°	0.5°	F	/	增加电镀规格 (先冲后镀)	sunquan	11-02/17

Singatron Enterprise Co., Ltd.				
TITLE	1.25mm Crimp Style Connectors Terminal			
DWN	劉 娜	PART NO.	2WT1258-TXX	
CHKD	周家慶	SCALE	1:1	UNIT: mm
APVD	張育瑞	SIZE:	A3	SHEET: 1 OF 1 REV: F
CUSTOMER COPY				