

■ SPECIFICATIONS

- Voltage Rating : 300 - 600V AC/DC
- Current Rating : 9 -15A AC/DC
- Withstanding Voltage : 1,500V AC/minute
- Insulation Resistance : 1,000MΩ min.
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20mΩ max.


■ TERMINAL

△ Part No. : 2WT2000H-TX

① Applicable wires : TH : AWG# 14 - 18  
TL : AWG# 18 - 22

- Material : Brass
- Finish : Tin plated
- Thickness : 0.25mm
- Q' ty : 2WT2000H-TH: 3,500 pcs./Reel  
2WT2000H-TL : 5,000 pcs./Reel

Part No.	Dimensions(mm)±0.4			
	A	B	C	D
2WT2000H-TH	4.80	4.85	2.90	3.70
2WT2000H-TL	4.10	3.20	2.60	2.30



TOLERANCE	LTR	REVISION RECORD	NAME	DATE	LTR	REVISION RECORD	NAME	DATE
.0	±0.30	1	删除舊料號	吳弘文	2013/12/02	1		
.00	±0.20	2	修正產品外觀	吳弘文	2013/12/09	2		
.000	±0.10	3	增加端子捲繞方向圖	吳弘文	2014/10/24	3		
ANGLE								
0°	±1°	4						
.0°	±	5						
SHEET	1/1	6						

Singatron Enterprise Co., Ltd.

TITLE	2.00mm Power Connectors Terminal		
DWN	吳弘文	PART NO.	2WT2000H-TX
CHKD	周慈雲	SCALE	1:1 UNIT: mm
APVD	張育瑞	SIZE: A3	SHEET: 1 OF 1 REV: a3

Conforms to The RoHS Instruction

CUSTOMER COPY