

REV	ECN.NO.	REVISIONS	REV.DRAWN	DATE
C		更改料带定位孔位置	YU	07-09/06
D	08083	增加端子头部0.1°0.15倒角	Yuqilong	08-08/18
E	09181	头部加长0.15	Asimo	09-10/30

SPECIFICATIONS

- . Rated Voltage : 100V AC/DC
- . Rated Current : 0.5A AC/DC
- . Withstanding Voltage : 300V AC/minute
- . Insulation Resistance : 500MΩ min
- . Temperature Range : -40°C to +85°C
- . Contact Resistance : 60mΩ max

TERMINAL:

- . Part No. Legend: 2WT2015-TXX

Gold Plated G0: Au>0.8μ" Ni>30μ"
G1: Au>3μ" Ni>30μ"
G2: Au>5μ" Ni>50μ"
G3: Au>8μ" Ni>50μ"
G4: Au>15μ" Ni>50μ"

- . Material: Phos.Bronze
- . Applicable Wires : AWG#30&32
- . Thickness : 0.15x12.0mm
- . Q'ty : 15,000pcs/Reel

Singatron Enterprise Co., Ltd.

TITLE		1.00 mm pitch Board to Wire Connectors		
DWN	Asimo 2009/10/30	PART NO. 2WT2015-TXX		
CHKD	XUWEI 2009/10/30	SCALE 1:1	UNIT: mm	①
APVD		SIZE: A3	SHEET:1 OF 1	REV: E
CUSTOMER COPY				

