



■ SPECIFICATIONS

- △ Current Rating : 22 AWG 3.0A AC/DC
24 AWG 2.0A AC/DC
26 AWG 1.0A AC/DC
28 AWG 0.8A AC/DC
- Voltage Rating : 250V AC/DC
- Withstanding Voltage : 1,000V AC/minute
- Insulation Resistance : 1,000M Ω min.
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20m Ω max.

■ TERMINAL

- △ Part No. : 2WT2017-XXTX^①
- △ ① PBT : Phos. Phor Bronze, Stamping after tin plated
- △ TP : Brass, Stamping before tin plated
- T : Pre-Tinned Copper Alloy
- Thickness : 0.15mm
- Applicable Wire : 22~28 AWG
- Mates With : 2WB2017-XXx2
- Q'ty : 10,000 Pcs/Reel

TOLERANCE	LTR	REVISION RECORD	NAME	DATE	LTR	REVISION RECORD	NAME	DATE
.0	±0.3	△ 增加3D圖&尺寸標註變更增加黃銅選項	林豐盛	11/03/29	△			
.00	±0.2	△ 依規格書修正規格，變更料號選項	張逸維	12/11/01	△			
.000	±0.1	△ 恢復原T選項	張逸維	12/11/01	△			
ANGLE		△						
0°	±1°	△						
.0°	±	△						
SHFFT	1/1	△						

Singatron Enterprise Co., Ltd.			
TITLE	2.00mm Crimp Style Connectors Terminal		
DWN	張逸維	PART NO. 2WT2017-XXTX	
CHKD	黃科源	SCALE 1:1	UNIT: mm
APVD	張育瑞	SIZE: A3	SHEET: 1 OF 1 REV: a3
CUSTOMER COPY			

CUSTOMER
Conforms to The RoHS Instruction