



■ SPECIFICATIONS

- Voltage Rating : 300V AC/DC
- Current Rating : 6A AC/DC
- Withstanding Voltage : 1,500V AC/minute
- Insulation Resistance : 1,000M Ω min.
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20m Ω max.

■ TERMINAL

- Part No. : **2WT23131BS-2**
- Applicable Wires : AWG # 20-26
- Material : Brass
- Finish : Tin Plated
- Thickness : 0.2 mm
- Q' ty : 7,000 pcs./Reel

| TOLERANCE | | LTR | REVISION RECORD | DATE | LTR | REVISION RECORD | DATE |
|-----------|-----------|-----|-----------------|----------|----------------------------------|-----------------|------|
| .0 | ± 0.3 | ECR | RoHS compliant | 06/04/01 | | | |
| .00 | ± 0.2 | ECR | 200608-003 | 06/08/10 | | | |
| .000 | ± 0.1 | ECR | 200706-003 | 07/06/04 | | | |
| ALL | \pm | | | | | | |
| ANGLE | | | | | CUSTOMER | | |
| 0° | \pm | | | | Conforms to The RoHS Instruction | | |
| .0° | \pm | | | | | | |

Singatron Enterprise Co., Ltd.

| | | | |
|----------------------|---|----------|-----------------------|
| TITLE | $\phi 1.3$ mm Power Connectors Terminal | | |
| DWN | 黃科源 | PART NO. | 2WT23131BS-2 |
| CHKD | 林陳鏞 | SCALE | 1:1 UNIT: mm |
| APVD | 林陳鏞 | SIZE: A3 | SHEET: 1 OF 1 REV: a2 |
| CUSTOMER COPY | | | |