



■ **SPECIFICATIONS**

- Voltage Rating : Pitch : 6.7mm 600V AC/DC
Pitch : 5.03mm 250V AC/D
- Current Rating : Pitch : 6.7mm 17A AC/DC
Pitch : 5.03mm 12A AC/DC
- Withstanding Voltage : 2,000V AC/minute
- Insulation Resistance : 1,000MΩ min.
- Temperature Range : -40°C~+105°C
- Contact Resistance : 20mΩ max.

■ **TERMINAL**

- Part No. : 2WT2330BS-2 X
- Product Code : ①
- ① Crimp Type :
Blank : Normal Type
L : Low Type
- Applicable Wires :
2WT2330BS-2 : AWG# 14 - 20
2WT2330BS-2L : AWG# 18 - 22
- Material : Brass
- Finish : Tin Plated
- Thickness : 0.25mm
- Q'ty : 2WT2330BS-2 : 5,000 pcs/Reel
2WT2330BS-2L : 3,500 pcs/Reel

TOLERANCE	LTR	REVISION RECORD	NAME	DATE	LTR	REVISION RECORD	NAME	DATE
.0	±0.30	①	200605-013	陳文松	2006/05/26	②		
.00	±0.20	②	依規格書修改SPEC. 合併2330BS-2L	張逸維	2013/06/10	③		
.000	±0.10	③	增加端子捲繞方向圖	吳弘文	2014/10/23	④		
ANGLE		④	修正側視圖	吳弘文	2014/10/28			
0°	±1°	⑤						
.0°	±	⑥						
SHEET	1/1	⑦						

Singatron Enterprise Co., Ltd.

TITLE	φ2.36mm Power Connectors Terminal			
DWN	吳弘文	PART NO.	2WT2330BS-2X	
CHKD	周慈雲	SCALE	1:1	UNIT: mm
APVD	張育瑞	SIZE	A3	SHEET: 1 OF 1
		REV	a4	
CUSTOMER COPY				

CUSTOMER
Conforms to The RoHS Instruction