



■ SPECIFICATIONS

- Current Rating : 3A AC/DC
- Withstanding Voltage : 1,500V AC/minute
- Insulation Resistance : 500MΩ min
- Temperature Range : -25°C to +85°C
- Contact Resistance : 10 milliohms Max.

■ TERMINAL

- Part No. : 2WT6504-TX

① Material: Blank : Phos. Bronze
B : Brass

- Applicable Wires : AWG# 22 - 28
- Finish : Tin Plated
- Thickness : 0.2mm
- Q' ty : 7,000 pcs./Reel

TOLERANCE	LTR	REVISION RECORD	NAME	DATE
.0	±0.30	▲1 產品材質變更	林文彬	2006/12/30
.00	±0.20	▲2 合併圖面&修改料號敘述	王誠賢	2011/07/25
.000	±0.10	▲3 增加端子捲繞方向圖	吳弘文	2014/10/24
ANGLE				
0°	±1°	▲5		
.0°	±	▲6		
SHEET	1/1	▲7		

Singatron Enterprise Co., Ltd.				
TITLE	2.50mm Wire to Wire Connector			
DWN	吳弘文	PART NO. 2WT6504-TX		
CHKD	周慈雲	SCALE 1:1	UNIT: mm	④
APVD	張育瑞	SIZE: A3	SHEET: 1 OF 1	REV: a3
CUSTOMER COPY				