



SPECIFICATIONS

- Current Rating : 3A AC/DC
- Withstanding Voltage : 1000V AC/minute
- Insulation Resistance : 1000M Ω min
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20m Ω max

TERMINAL

- Part No.: 2WB8001-TXX(XX)

Code No: ① ②

- ① T : Standard Process, Brass
- TP : Stamping before Plated, Brass
- PBT : Standard Process, Phosphor Bronze
- △ PBTP : Stamping before Plated, Phosphor Bronze
- ② Plated : Blank : Tin Plated(80u" Tin-Lead Plating, 15u"Min Nickel Under Plating)
- △ G : Gold Flash
- G1 : 1. Gold 30u"(Phosphor Bronze)
- 2. Selec Gold(Brass)
- G2 : Gold 10u"(Brass)
- G6 : Gold 5u"(Brass)
- Applicable Wires : AWG # 22 - 28
- Material : Refer the above narrative
- Thickness : 0.2 mm
- Q'ty : 10000 pos./Reel

TOLERANCE	LTR	REVISION RECORD	NAME	DATE
.0	△			
±0.30	△			
±0.20	△			
±0.10	△			
ANGLE	△			
±1°	△			
±	△			
SHEET	1/1			

Singatron Enterprise Co., Ltd.				
TITLE	2.54mm Crimp Style Connectors Terminal	CHKD	APVD	SCALE
DWN	Tom Lee	Erin Chou	Tom Smith	1:1
PART NO.	2WT8001-TXX(XX)	SCALE	SIZE: A3	1:1
UNIT:	mm	SHEET:	1 OF 1	REV: 04
CUSTOMER COPY				