







2WW23158A-02





2WW23158A-06





2WW23158A-12





2WW23158A-03



2WW23158A-09



2WW23158A-15



2WW23158A-04

■ SPECIFICATIONS

- Voltage Rating : 250 V AC/DC
- Current Rating : 5 A AC/DC
- Withstanding Voltage : 1,500V AC/minute
- Insulation Resistance : 1,000MΩ min
- Temperature Range : - 40°C to + 105°C

■ HOUSING

- Part No. : 2WW23158A-XXX
- 2WW23158A-XX : GP Produces
- 2WW23158A-0XX : Non GP Produces
- Poles : 2, 3, 4, 6, 9, 12, 15
- Material : Nylon 66 UL94V-2
- Q' ty : 1,000 pcs./Bag

TOLERANCE		LTR	REVISION RECORD	DATE
.0	±0.3			
.00	±0.2			
.000	±0.1			
ALL	±			
ANGLE				
0°	±			
.0°	±			

Singatron Enterprise Co., Ltd.				
TITLE	ø1.58mm Power Connectors Housing			
DWN	邱森瑞	PART NO. 2WW23158A-XX		
CHKD	林勇生	SCALE 1:1	UNIT: mm	⊕ ↻
APVD	林陳鏗	SIZE: A3	SHEET: 1 OF 1	REV: a
CUSTOMER COPY				