



■ SPECIFICATIONS

- Voltage Rating : 250 V AC/DC
- Current Rating : 5 A AC/DC
- Withstanding Voltage : 1,500V AC/minute
- Insulation Resistance : 1,000M Ω min
- Temperature Range : - 40 $^{\circ}$ C to + 105 $^{\circ}$ C
- Contact Resistance : 20m Ω max

■ HOUSING

- Part No. : 2WW23158B-XXE

- ① Poles : 1, 2, 3, 4, 5, 6, 9, 12, 15
- Material : Nylon 66 UL94V-2
- Q' ty : 1,000 pcs./Bag

TOLERANCE	LTR	REVISION RECORD	NAME	DATE	LTR	REVISION RECORD	NAME	DATE
.0	±0.30	△	刪除舊料號，更新圖框	吳弘文	2014/12/09	△		
.00	±0.20	△			△			
.000	±0.10	△			△			
ANGLE		△			△			
0°	±1°	△			△			
.0°	±	△			△			
SHEET	1/1	△						

Singatron Enterprise Co., Ltd.

TITLE	Ø1.56mm Power Connectors Housing			
DWN	吳弘文	PART NO. 2WW23158B-XXE		
CHKD	周慈雲	SCALE 1:1	UNIT: mm	⊕ ↺
APVD	張育瑞	SIZE: A3	SHEET: 1 OF 1	REV: a1

CUSTOMER
Conforms to The RoHS Instruction

CUSTOMER COPY