





2WW2330-02





2WW2330-03




2WW2330-04




2WW2330-04





2WW2330-2x2





2WW2330-06



2WW2330-06





2WW2330-01





- SPECIFICATIONS**
- Current Rating : 12A AC/DC
  - Voltage Rating : 250V AC
  - Withstanding Voltage : 2,000V AC/minute
  - Insulation Resistance : Low -Signal Level
  - Temperature Range : -40°C to +105°C
  - Contact Resistance : 20mΩ max

- RECEPTACLE**
- Part No. : 2WW2330-XX
  - Poles No. : 1, 2, 3, 4, 2x2, 6, 9, 12, 15
  - Material : Nylon 66 UL94V-2
  - Package : Bag



2WW2330-09



2WW2330-12



2WW2330-15



TOLERANCE	LTR	REVISION RECORD	NAME	DATE	LTR	REVISION RECORD	NAME	DATE
.0	±0.35	△ ECR 200507-004	曲智浩	05/07/08	△			
.00	±0.20	△ ECR 200811-024	黃科源	08/11/27	△			
.000	±0.10	△ 遺失			△			
<b>ANGLE</b>		△ ECR 201004-001	黃科源	10/04/12				
0°	±1°	△ ECR 201103-013	王誠賢	11/03/29				
.0°	±	△ 依規格書修改Spec.	張逸維	13/05/21				
SHEET	1/1							

Singatron Enterprise Co., Ltd.

TITLE	5.03mm wire to wire Power Connector, Without Ear			
DWN	張逸維	PART NO.	2WW2330-XX	
CHKD	黃科源	SCALE	1:1	UNIT: mm
APVD	張育瑞	SIZE: A3	SHEET: 1 OF 1	REV: a6
<b>CUSTOMER COPY</b>				

CUSTOMER  
Conforms to The RoHS Instruction