




1. ELECTRICAL CHARACTERISTICS:
- 1-1. DIELECTRIC WITHSTANDING VOLTAGE: 500V AC FOR ONE MINUTE
 - 1-2. INSULATION RESISTANCE: 100MΩ MIN. MEASURED BY 500 VDC
 - 2. TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.
 - 3. HALOGEN FREE PRODUCT IDENTIFICATION MARK ON JACK: 
 - 4. HALOGEN FREE PRODUCT IDENTIFICATION LABEL ON PACKAGING: 
 - 5. FOR REFLOW SOLDERING LEAD-FREE PROCESS.

RECOMMEND P.C.B LAYOUT
TOP VIEW (TOLERANCES: ±0.05)

NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
C	CAP	1	HIGH THERMOPLASTIC TEMP. UL 94V-0	BLACK
B	TERMINAL	3	BRASS; 0.50T	GOLD FLASH OVER Ni 60U*
A	BODY	1	HIGH THERMOPLASTIC TEMP. UL 94V-0	BLACK

UNLESS OTHERWISE SPECIFIED TOLERANCES

DECIMALS:	ANGLES:
X :±0.5	X :±2°
XX :±0.3	X.X :±1°
XXX :±0.2	

 Singatron Enterprise Co., Ltd.
信登企業股份有限公司

TITLE: 3.75PITCH 3 PIN BATTERY CONN.
DWG Sky PART NO. 2BA3019-003111
CHKD Boye SCALE: 4:1 UNIT: mm
APVD Max SIZE: A3 SHEET: 1 OF 1 REV: A

REV	ECN NO OR DESCRIPTION	REVISED	DATE
A	PDR NO. S100205-1A	Sky	2010.07.13

CUSTOMER COPY