



Recommended PCB Layout
 <BOTTOM VIEW>
 * TOLERANCE FOR PCB LAYOUT IS ±0.05

SPECIFICATIONS:
 SEE 20J-802B SERIES SPECIFICATIONS.

13	SHIELDING	1	BRASS 0.2t	NICKEL PLATING
12	CONTACT #2S	1	BRASS 0.5t	TIN PLATING
11	CONTACT #3N	1	PHOSPHOR BRONZE 0.3t	TIN PLATING
10	CONTACT #5	1	BRASS 0.4t	TIN PLATING
9	DRIVE IC(RX)	1		
8	OPTO SPRING	2	SUS 301	
7	OPTO GATE	2	PA-66 UL 94V-0	PINK COLOR(701C)
6	OPTO FRAME	1	PA-66 UL 94V-0	BLACK COLOR
5	OUTER CONTACT	1	BRASS 0.2t	NICKEL PLATING
4	WASHER RCA	1	PBT UL 94V-0	ORANGE COLOR(157C)
3	COVER	1	PBT UL 94V-0	BLACK COLOR
2	RCA HOUSING	1	PBT UL 94V-0	BLACK COLOR
1	OPTO HOUSING	1	PBT UL 94V-0	BLACK COLOR
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR

UNLESS OTHERWISE SPECIFIED TOLERANCES

DECIMALS: ANGLES:
 X.X :±0.3 X.X :±3°
 X.XX :±0.2

Singatron Enterprise Co., Ltd.
 信管企業股份有限公司

TITLE	OPTO W/ RCA JACK, SHUTTLE TYPE			
DWN	Beryl/2005.5.24	PART NO.	20J-802B-R02	
CHKD	Kan 2005.5.24	SCALE:2/1	UNIT:	MM
APVD	Allen 2005.5.24	SIZE: A3	SHEET:1 OF 1	REV: A