



REV.	ECN NO.	OR DESCRIPTION	REVISED	DATE
A	PDR NO.:	T090423-4A	Sidley	2009.05.04
B	ECN NO.:	S091009	Tom	2009.10.19

- SPECIFICATIONS:**
- ELECTRICAL CHARACTERISTICS:**
 - 1-1. RATING: 12V 1A
 - 1-2. CONTACT RESISTANCE: 30mΩ MAX(INITIAL).
 - 1-3. DIELECTRIC VOLTAGE WITHSTAND: 500V AC FOR ONE MINUTE
 - 1-4. INSULATION RESISTANCE: 100MΩ MIN. MEASURED BY 500 VDC
 - MECHANICAL CHARACTERISTICS:**
 - 2-1. INSERTED FORCE : 3.5 KGS MAX.
 - 2-2. WITHDRAWAL FORCE : 0.3~4.0 KGS
 - LIFE TEST:** 5,000 CYCLES MIN.
 - PACKAGING:** TAPE & REEL
 - TO CONFORM TO SINGATRON HAZARDOUS SUBSTANCE FREE SPEC.**
 - GREEN PRODUCT IDENTIFICATION MARK ON JACK:**
 - GREEN PRODUCT IDENTIFICATION LABEL ON PACKAGING:**
 - FOR LEAD-FREE PROCESS.**



J	IC DRIVER	1	EPOXY/COA-C19400	
I	SHIELDING	1	COPPOR ALLOY	N: 60U" Min
H	EARTH SPRING-A	1	PHOSPHOR BRONZE	GOLD FLASH OVER 50U" Ni Min
G	EARTH SPRING-B	1	PHOSPHOR BRONZE	GOLD FLASH OVER 50U" Ni Min
F	EARTH TERMINAL	1	PHOSPHOR BRONZE	GOLD FLASH OVER 50U" Ni Min
E	TIP SPRING	1	PHOSPHOR BRONZE	GOLD FLASH OVER 50U" Ni Min
D	RING SPRING	1	PHOSPHOR BRONZE	GOLD FLASH OVER 50U" Ni Min
C	CASE	1	PA-9T+30%GF	BLACK
B	COVER	1	PA-9T+30%GF	BLACK
A	BODY	1	PA-9T+30%GF	BLACK
NO	DESCRIPTION	QTY	MATERIAL	PLATING & COLOR
UNLESS OTHERWISE SPECIFIED TOLERANCES				
DECIMALS: ANGLES:				
X	:±0.5	X	:±2°	
X.X	:±0.3	X.X	:±1°	
X.XX	:±0.2			
Singatron Enterprise Co., Ltd. 信營企業股份有限公司				
TITLE Ø3.5 PHONE JACK (WITH IC)				
DWN	Tom	2009.10.19	PART NO. 2SI-D373-D05	
CHKD	Lussen	2009.10.19	SCALE: 3/1	UNIT: mm
APVD	Wu	2009.10.19	SIZE: A3	SHEET: 1 OF 1
REV: B				
CUSTOMER COPY				